STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION



NOTES

Detail I - With Bar Splicer or Couplers: Connect one (1) 1"x7"x10" steel R to the top layer of couplers with $2^{-5}8$ " ϕ bolts screwed to coupler at approximate $\[\ell \]$ of each barrier panel.

Detail II - With Extended Reinforcement Bars: Connect one (1) 1"x7"x10" steel P to the concrete slab or concrete wearing surface with 2-58'\psi Expansion Anchors or cast in place inserts spaced between the top layer of reinforcement at approximate © of each barrier panel.


Cost of anchorage is included with Temporary Concrete Barrier.

The 1" x 7" x 10" plate shall not be removed until stage II construction forms and all reinforcement bars are in place and the concrete is ready to be placed.


***Dimension shown is minimum required embedment into concrete.


If hot-mix asphalt wearing surface is present, minimum embedment

shall be in addition to wearing surface depth. ****If existing deck beam is to remain in place after stage construction, embedment shall only be into wearing surface and not into existing deck beam concrete.



SECTIONS THRU SLAB





STEEL RETAINER P 1" x 7" x 10"

*Required only with Detail II

DESIGNED Dhruv P. Narielwala CHECKED Stephen M. Ryan h.t. duong CHECKED DPN/SMR R-27

9-3-07

DETAIL I

When "A" is 3'-6" or less, the temporary concrete

to Detail I or Detail II. No anchorage is required

when "A" is greater than 3'-6".

barrier shall be anchored to the new slab according

**Wood blocks may be omitted when required to provide minimum stage traffic lane width. When the wood blocks are omitted, the concrete barrier shall be in direct contact with the steel retainer plate.

TEMPORARY CONCRETE BARRIER FOR STAGE CONSTRUCTION F.A.P. RT. 330 SEC. 104B-3-BR WILL COUNTY STATION 149+06.00 STRUCTURE NO. 099-4649